

Technical Specifications

ROTOR SPECIFICATIONS	
OVERALL LENGTH	285 in
CONTOUR LENGTH	277 in
HEAD LENGTH*	8.00 in
HEAD DIAMETER*	5.50 in
MAJOR DIAMETER	5.186 in
MINOR DIAMETER	4.014 in
CREST-TO-VALLEY	4.600 in
ECCENTRICITY	0.293 in
THREAD TYPE	By Request


STATOR SPECIFICATIONS	
OVERALL LENGTH	300 in
CONTOUR LENGTH	284 in
TUBE OD	8.00 in
TUBE ID	6.25 in
CUTBACK*	8.00 in
WEIGHT	1592 lb
MATERIAL	4140
THREAD TYPE	By Request

*May be changed at customer request

PERFORMANCE	
FLOW RANGE	400-900 gpm
SPEED RANGE	64-144 rpm
RPG	0.160 rev/gal
OFF BOTTOM PRESS	210 psi
TORQUE/PSI	15.90 ft-lbs/psi
VECTOR TOLERANCE	± 0.010 in

STATOR MIN. DIA. (in)	NOMINAL FIT @ 70°F (in)
K5	K5
1 X US	
STD 4.584	0.016
0.5 X OS	
1 X OS	
1.5 X OS	
2 X OS	

ELASTOMER PERFORMANCE		
	K5	
MAX DIFF PRESS	1,387	psi
MAX TORQUE	22,053	ft-lb
MAX HP	444	hp
STALL DIFF PRESS	2,081	psi
STALL TORQUE	33,080	ft-lb
FIT INCREASE / °F	0.000309	in / °F



The performance data contained herein is for REFERENCE ONLY. Performance data and specifications for this model are generated based on shop/nominal fit between rotor and stator. ArcoTech power sections are designed to perform optimally at the temperature range recommended for each group/fit. Downhole conditions may alter the performance. Downhole performance is included as a prediction of how the stator is expected to perform in downhole conditions for any group fit.

